

Stackable Battery

IonStack Series-SL

IS5-55-SL



Plug&Play
Installation, Less
Wiring



Top-Notch LFP Class A
Cell/Strict Capacity
Grading



IP20-Certified,
Suitable for More
Indoor Applications



Modular Design, 5 -
15 kWh Flexible
Configuration



Precise Voltage
/Temperature/SOC
Detection

DATASHEET

Model	IS5-55-1-SL	IS5-55-2-SL	IS5-55-3-SL
Product Pattern			
Battery Module Type	LiFePO4	LiFePO4	LiFePO4
Inverter Module Quantity	1		
Operating Voltage (Input)	90-140Vac $\pm$ 3V		
Operating Voltage (Output)	110/120Vac $\pm$ 5%		
Nominal Capacity	5.5KW		
Max. Continuous Discharge Power	5.5KW		
MAX PV Input Power	8.5KW		
Maximum PV Input Voltage	500Vdc		
Maximum PV Input Current	27A		
Best PV Voltage	360~430Vdc		
Inverter Module Dimensions [W/D/H] (mm)	590*155*400mm		
Inverter Module Weight [kg]	19kg		
Battery Module Quantity	1	2	3
Nominal Energy	5KWh	10kWh	15KWh
Usable Energy	5KWh	10kWh	15KWh
Dimensions [W/D/H] (mm)	590*155*860mm	590*155*1260mm	590*155*1660mm
Weight [kg]	80kg	135kg	190kg
Battery Module Dimensions [W/D/H] (mm)	590*155*400mm		
Battery Module Weight [kg]	55kg		
Operating Voltage	43.2-58.4V		
Recommended Depth of Discharge (DOD)	90%		
Charging Temperature Range	0-60℃		
Discharging Temperature Range	-10-60℃		
Communication	RS485/CAN		
Cycle life	2500 circulate		
Protection Level	IP20		
Maximum Parallel Connection Quantity	6		
Certification	MSDS/UN38.3		
Compatible Inverters	SUNSYN/PYLON/GROWAT/DEYE/GOODWE/SOFAR/MEGAREVO		

This material is for reference only and does not constitute any commitment regarding product performance or specifications. Product design and specifications may be changed at any time.

The Company assumes no liability for any losses arising from the use of this material or the products