

IW-12.8V 150Ah

LITHIUM IRON PHOSPHATE BATTERY



High cycle life
>3000 cycles @80%
DOD for effectively
lower total cost of
ownership.



Longer service life
Stable,
low- maintenance
batteries with smart
SOC monitoring.



**Built in circuit
protection**
BMS are incorporated
against abuse.



Quickly recharge
Superior charge-
discharge efficiency
minimizes downtime
for higher
productivity.



**Extreme heat
tolerance**
Reliable up to +60 ° C,
ideal for
high- temperature
scenarios.

DATASHEET

ELECTRICAL PERFORMANCE	
Nominal Voltage	12.8 V
Nominal Capacity	150 Ah
Capacity @ 8.4A	300 min
Energy	1920 Wh
Resistance	$\leq 50 \text{ m}\Omega$ @ 50% SOC
Self Discharge	<3% / Month
Cells	32700 Cell 6000mAh
CHARGE PERFORMANCE	
Recommended Charge Current	30 A
Maximum Charge Current	75 A
Recommended Charge Voltage	14.6 V
Charge Cut-Off Voltage	<15.2 V (0.5 ~ 1.5 s)
Reconnect Voltage	>14.4 V
Balancing Voltage	<14V
Maximum Batteries in Parallel	4
DISCHARGE PERFORMANCE	
Continuous Discharge Current	75 A
Max Discharge Current	120 A
BMS Discharge Cut-Off Current	300 A (5 ~ 15 ms)
Recommended Low Voltage Disconnect	10 V
BMS Discharge Cut-Off Voltage	>8.4 V (50 ~ 150 ms)
Reconnect Voltage	>10 V
Short Circuit Protection	200 ~ 600 μs
TEMPERATURE PERFORMANCE	
Discharge Temperature	-4 ~ 140 °F (-20 ~ 60 °C)
Charge Temperature	32 ~ 113 °F (0 ~ 45 °C)
Storage Temperature	23 ~ 95 °F (-5 ~ 35 °C)
BMS High Temperature Cut-Off	149 °F (65 °C)
Reconnect Temperature	118 °F (48 °C)
MECHANICAL PERFORMANCE	
Dimension (L x W x H)	483 x 170 x 240 mm 19.01 x 6.69 x 9.45"
Approx. Weight	17.8 kg
Terminal Type	M8
Terminal Torque	80 ~ 100 in-lbs (9 ~ 11 N-m)
Case Material	ABS
Enclosure Protection	IP65
COMPLIANCE	
Certifications	CE, UN38.3, UL1642 & IEC62133
Shipping Classification	UN 3480, CLASS 9

This material is for reference only and does not constitute any commitment regarding product performance or specifications. Product design and specifications may be changed at any time.

The Company assumes no liability for any losses arising from the use of this material or the products